

Hydrokleen Wastewater Filtration

ACF3 - Multimedia Filtration

The ACF3 is designed for flow thru filtration rates up to 12 GPM and incorporates two (2) separate filtration modules. Each module incorporates a filtration media that is selected to assist with filtration or recycling requirements. Solids, oils & grease (hydrocarbons) or metals filtration, choose to solve any two (2) filtration requirements with the ACF3. Every Hydrokleen filtration systems that feature PLC operation can also incorporate pH control, bacteria, pathogen, odor elimination and more, along with remote system monitoring. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance. Hydrokleen filtration / recycling systems are UL-979 and CSA certified, and conform to CE standards.

Standard Features

- Overflow Protection
- Gravity Flow Through Design
- Self-cleaning Tank
- Polishing Loop for Fine Solids
- Emulsified Oils, and Hydrocarbon Removal
- Polishing Loop for Metals and Chemical Removal
- PLC Controls

Optional Features

- Service Indicator Beacon
- Factory System Monitoring, PLC Touch Screen
- Pressurized Discharge To Drain
- [Biological Odor Control and Hydrocarbon Elimination](#)
- De-foam Control
- [pH Control](#)
- Ozone Bacteria Control
- Full System Vented Enclosure



Specifications

Flow Rate - GPM (LPM)	12 (45.4)
Dimensions, Inches (cm)	142.5 (362) L X 37.5 (95.3) W X 75 (190.5) H
Weight, Lbs (kg)	1466 (665)

	Standard
Volts (60Hz)	230V-1P
Amps (60Hz)	18

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)