

Hydrokleen Wastewater Filtration

SPL30 - Water Filtration & Recycling System

The SPL30 is designed for flow thru filtration rates up to 50 GPM and incorporates one (1) filtration module. This module incorporates a filtration media that is selected to assist with filtration or recycling requirements. Solids, oils & grease (hydrocarbons) or metals filtration, choose to solve any one (1) filtration requirement with SPL30. Every Hydrokleen filtration systems that feature PLC operation can also incorporate pH control, bacteria, pathogen and odor elimination and more, along with remote system monitoring. Contact a Hydro Engineering, Inc. project manager for complete system design and application assistance. Hydrokleen filtration / recycling systems are UL-979 and CSA certified, and conform to CE standards.

Standard Features

- Overflow Protection
- Gravity Flow Through Design
- Choose Filtration Module for Fine Solids, Hydrocarbon, or Metals Removal
- PLC Controls

Optional Features

- 210 500 Or 1050 or Gallon Tank
- Service Indicator Beacon
- Factory System Monitoring, PLC Touch Screen
- Pressurized Discharge To Drain
- Auto Dosing For Biological Odor Control and Hydrocarbon Elimination
- Auto Dosing For De-foam
- [pH Control](#)
- Ozone Bacteria Control
- Full System Vented Enclosure



Specifications

Flow Rate - GPM (LPM)	50 (189.3)
Dimensions, Inches (cm)	54 (137.2) L X 36 (91.4) W X 75 (190.5) H
Weight, Lbs (kg)	980 (444.5)

	Standard
Volts (60Hz)	230V-1P
Amps (60Hz)	15

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)