

Hydroblaster Pressure Washer

25/500 E - Water Cannon for Equipment Washing

Hydroblaster Model 25/500E Water Cannon provides industries most efficient and effective high-volume rinse or decontamination possible. Precision design balance of flow and pressure coupled with premier wand/nozzle combination optimize performance results. Operators have simple on-the-fly spray adjustment flexibility range from full fan to direct stream.

Applications can include heavy equipment decontamination, aircraft high volume rinse, or any application where engineered perfection of this Hydroblaster water cannon technology can benefit. Contact a Hydro Engineering, Inc. project manager for more information, application assistance or complete system design.

Model 25/500E equipment is certified to UL-1776, CSA, and conform to CE standards.

Standard Features

- 208/230 Volt
- Formed Steel Frame
- 500 Gallon (1,893 Liter) Cone Bottom Tank
- Trigger Gun Wand and Nozzle Assembly
- Hour Meter

Optional Features

- No Tank With Flooded Suction Inlet
- 210 Gallon Cone Bottom Tank
- Manual or Automatic Tank Sludge Drains
- 50 Hz Motor
- Remote On/Off NEMA 4X Enclosure
- Stainless Steel Cover and Panels
- Select 50', 75', or 100' High Pressure Discharge Hose
- Hose Reels, Manual or Spring Retract



Specifications

Volume - GPM (LPM)	25 (94.6)
Pressure - PSI (BAR)	500 (34.5)
Electric Motor - HP (KW)	10 (7.46)
Dimensions, Inches (cm)	112 (284.5) L X 43 (109) W X 96 (244) H
Weight, Lbs (kg)	1166 (529)

Standard

Volts (60Hz)	230V-3P	230V-1P	460V-3P
Amps (60Hz)	25	46	14

Pricing

For complete pricing details, Submit a quote online below.

[Get a Quote](#)